HYDRONIC HEATING SYSTEM WORKSHEET



OLO OF TRITLE OF E (REVISED OF 14)	ONEII ONININ EINEROT OOMMIOOION
CERTIFICATE OF COMPLIANCE	CF1R-PLB-01-E
Hydronic Heating System Worksheet	(Page 1 of 1)
Project Name:	Date Prepared:

A. Pipe Heat Loss Worksheet				
	01	02	03	04
Р	Pipe Diameter (inches)	Pipe Heat Loss Factor (kBtu/year/ft)	Pipe Length (ft)	Pipe Heat Loss (kBtu/year)
				:01
				11000
05	05 Sum of all pipe heat losses (kBtu/hr)		100	
06	Average Hourly Pipe Hea	t Loss (Btu/hr)	(0)	W.

B. Hydronic System Calculations for Large Storage Gas				
01	Recovery Efficiency/AFUE of the water heater or boiler (unitless)	3 3 5		
02	Average Hourly Pipe Heat Loss (Btu/hr)	400		
03	Rated Input of water heater or boiler (Btu/hr)	76,		
04	Standby Loss—percentage (if known)			
05	Standby Loss—Power (from appliance database, if known) (Btu/hr)	NO		
06	Pump Watts (Watts) (if applicable)	Y		
07	Pump Energy (Btu/hr)			
08	Effective AFUE			

Registration Date/Time: Registration Number: HERS Provider:

CERTIFICATE OF COMPLIANCE – USER INSTRUCTIONS	CF1R-PLB-01E
Hydronic Heating System Worksheet	(Page 1 of 1)

A. Pipe Heat Loss Worksheet

- 01 Enter all the different pipe diameters of the system.
- 02 Using the table below, determine the pipe heat loss factor for the corresponding pipe diameter
- 03 Enter the pipe length
- 04 Multiply line B02 by B03, this is the pipe heat loss
- 05 Enter the sum of all pipe heat loss
- 06 Divide line B05 by 8760 times 1000

Pipe Heat Loss Factor Lookup Table

es 1000		
Pipe Heat Loss Facto	or Lookup Table	cijoli, s
Pipe Nominal Diameter	Pipe Heat loss factor	135
.75	66.6	. 111
1.0	78.8	1 11-
1.5	100.3	0
	X O	

B. Hydronic System Calculations for Boiler or Large Storage Gas

- 01 Enter the Recovery Efficiency/AFUE from manufacturer's literature or the appliance database
- 02 Enter average hourly pipe heat loss sum A06 from section A above
- 03 Enter the rated input from manufacturer's literature or the appliance database
- 04 Enter the standby loss percent from manufacturer's literature or the appliance database. Can be skipped if unknown
- 05 Standby loss energy (from appliance database) is used if standby loss percent is not known. Enter the standby loss energy from manufacturer's literature or the appliance database.
- 06 Standby loss energy (calculated) is line A03 times line A04
- 07 Enter the pump watts

FOI W. N

- 08 Pump energy is line A06 times 3.414 / 1000. If unknown then default value is 0.2
- 09 Effective AFUE is [line A01 (line A02+ line A05 + (line A07 / line A03)]